

Tire size	Product code	Speed rating	Load Index	Load range	Sidewall	Uniform Tire Quality Grade (UTQG)	Max load (lbs)	Max inflation pressure (psi)	Approved rim width (in.)	Measured rim width (in.)	Section width (in.)	Tread depth (in 32nds)	Outside diameter (in.)	Revs per mile	MSRP*
35X12.50R17LT	357351294	P	119	D	BSL	n/a	3,000	50	8.5 - 11.0	10.00	12.5	19	34.8	597	\$313
LT225/75R16	357814294	P	115	E	BSL	n/a	2,680	80	6.0 - 7.0	6.00	8.8	19	29.3	714	\$208
LT245/75R16	357797294	P	120	E	BSL	n/a	3,042	80	6.5 - 8.0	7.00	9.8	19	30.5	686	\$206
LT265/75R16	357334294	P	123	E	BSL	n/a	3,415	80	7.0 - 8.0	7.50	10.5	19	31.7	660	\$230
LT285/75R16	357584294	P	126	E	BSL	n/a	3,750	80	7.5 - 9.0	8.00	11.3	19	33.1	637	\$246
LT315/75R16	357194294	P	127	E	BSL	n/a	3,860	65	8.0 - 10.0	8.50	12.3	19	34.8	605	\$277
LT235/85R16	357328294	P	120	E	BSL	n/a	3,042	80	6.0 - 7.5	6.50	9.3	19	31.7	659	\$204
LT265/70R17	357368294	P	121	E	BSL	n/a	3,195	80	7.0 - 8.5	8.00	10.7	19	31.7	660	\$228
LT285/70R17	357435295	P	121	D	OWL	n/a	3,195	65	7.5 - 9.0	8.50	11.5	19	33.0	638	\$291
LT275/65R18	357442088	P	123	E	BSW	n/a	3,415	80	7.5 - 9.0	8.00	11.0	19	32.1	651	\$314
LT325/65R18	357523294	P	127	E	BSL	n/a	3,860	65	9.0 - 12.0	9.50	13.0	19	34.8	597	\$343
LT275/70R18	357379294	P	125	E	BSL	n/a	3,640	80	7.0 - 8.5	8.00	11.0	19	33.4	630	\$299