




EXTENSA HP - SIZES AND SPECIFICATIONS

Printed: July 24, 2014

Tire Size	Load / Speed	Load ID	Sidewall	Product Code	Approved Rim Width Range (in.)	Weight (lbs.)	Tread Depth (1/32")	Inflated Overall Diameter (in.)	Inflated Overall Width (in.)	Static Loaded Radius (in.)	Max Load (lbs.)	Max Pressure (PSI)	UTQG	Revs Per Mile
195/50R15	86V	XL	BSW	195300	5.5-6.0-7.0	17	9.3	22.6	7.7	10.5	1168	50	360 A A	918
P195/55R15	84V	SL	BSW	195310	5.5-6.0-7.0	17	9.3	23.3	7.7	10.8	1102	51	360 A A	890
185/55R16	83V	SL	BSW	195810	5.0-6.0-6.5	17	9.2	24	7.6	11.1	1074	51	360 A A	865
195/50R16	84V	SL	BSW	195650	5.5-6.0-7.0	18	9.3	23.7	7.7	11	1102	51	360 A A	875
195/55R16	87V	SL	BSW	195670	5.5-6.0-7.0	19	9.3	24.4	7.9	11.3	1201	51	360 A A	851
205/45R16	87V	XL	BSW	195320	6.5-7.0-7.5	18	9.4	23.2	8	10.8	1201	50	360 A A	896
205/50R16	91V	XL	BSW	195330	5.5-6.5-7.5	20	9.4	24.1	8.2	11.1	1356	50	360 A A	864
205/55R16	94V	XL	BSW	195510	5.5-6.5-7.5	20	9.4	25	8.3	11.5	1477	50	360 A A	831
205/55R16	91V	SL	BSW	195660	5.5-6.5-7.5	21	9.4	24.9	8.4	11.5	1356	51	360 A A	835
215/55R16	97V	XL	BSW	195530	6.0-7.0-7.5	21	9.6	25.2	8.9	11.6	1609	50	360 A A	826
P225/50R16	91V	SL	BSW	195340	6.0-7.0-8.0	22	9.7	24.8	9.1	11.4	1367	51	360 A A	839
P225/55R16	94V	SL	BSW	195350	6.0-7.0-8.0	22	9.7	25.6	9	11.7	1477	51	360 A A	812
205/40R17	84V	XL	BSW	195420	7.0-7.5-8.0	18	9.4	23.5	8.4	11.1	1102	50	360 A A	882
205/50R17	93V	XL	BSW	195370	5.5-6.5-7.5	21	9.4	25.1	8.2	11.7	1433	50	360 A A	827
215/45R17	91V	XL	BSW	195380	7.0-8.0	21	9.6	24.6	8.2	11.5	1356	50	360 A A	843
215/50R17	95V	XL	BSW	195520	6.0-7.0-7.5	25	9.6	25.5	8.7	11.8	1521	50	360 A A	816
P215/55R17	93V	SL	BSW	195430	6.0-7.0-7.5	23	9.6	26.3	8.7	12.1	1433	51	360 A A	789
225/45R17	94V	XL	BSW	195390	7.0-7.5-	22	9.7	24.9	8.7	11.6	1477	50	360 A	835

					8.5								A	
P225/50R17	93V	SL	BSW	195440	6.0-7.0-8.0	24	9.7	25.9	8.9	12	1433	51	360 A A	802
P225/55R17	95V	SL	BSW	195360	6.0-7.0-8.0	25	9.7	26.7	9	12.3	1521	51	360 A A	778
235/45R17	97V	XL	BSW	195400	7.5-8.0-9.0	22	9.8	25.2	9.1	11.7	1609	50	360 A A	823
235/55R17	99W	SL	BSW	195740	6.5-7.5-8.5	28	9.8	27.2	9.6	12.5	1709	51	360 A A	765
245/40R17	95W	XL	BSW	195690	8.0-8.5-9.5	22	10	24.7	9.5	11.5	1521	50	360 A A	840
P245/45R17	95W	SL	BSW	195410	7.5-8.0-9.0	24	10	25.6	9.4	11.8	1521	51	360 A A	813
255/40R17	98W	XL	BSW	195750	8.5-9.0-10.0	24	10.1	25	10	11.6	1653	50	360 A A	830
215/35R18	84V	XL	BSW	195470	7.0-7.5-8.5	19	9.6	24	8.5	11.3	1102	50	360 A A	866
225/40R18	92V	XL	BSW	195450	7.5-8.0-9.0	22	9.7	25.1	8.9	11.8	1389	50	360 A A	827
225/50R18	99W	XL	BSW	195760	6.0-7.0-8.0	27	9.7	26.9	8.9	12.5	1709	50	360 A A	773
235/40R18	95V	XL	BSW	195460	8.0-8.5-9.5	23	9.8	25.4	9.4	11.9	1521	50	360 A A	817
235/50R18	101W	XL	BSW	195550	6.5-7.5-8.5	28	9.8	27.2	9.4	12.6	1819	50	360 A A	764
245/40R18	97W	XL	BSW	195500	8.0-8.5-9.5	24	10	25.7	9.6	12	1609	50	360 A A	808
245/45R18	100W	XL	BSW	195570	7.5-8.0-9.0	28	10	26.7	9.6	12.4	1764	50	360 A A	779
P245/55R18	102V	SL	BSW	195770	7.0-7.5-8.5	29	10	28.6	10	13.1	1874	51	360 A A	726
255/35R18	94W	XL	BSW	195620	8.5-9.0-10.0	26	10.1	25	10	11.7	1477	50	360 A A	832
255/45R18	103W	XL	BSW	195780	8.0-8.5-9.5	30	10.1	27	10	12.5	1929	50	360 A A	768
275/35R18	99W	XL	BSW	195630	9.0-9.5-11.0	27	10.3	25.5	10.7	11.9	1709	50	360 A A	814
225/30R20	85W	XL	BSW	195590	8.0	20	9.7	25.4	8.8	12.1	1135	50	360 A A	818
225/35R20	90V	XL	BSW	195490	7.5-8.0-9.0	21	9.7	26.3	8.9	12.4	1323	50	360 A A	791
245/35R20	95V	XL	BSW	195480	8.0-8.5-9.5	24	10	26.8	9.5	12.6	1521	50	360 A A	776

245/40R20	99W	XL	BSW	195610	8.0- 8.5 -9.5	28	10	27.7	9.6	13	1709	50	360 A A	749
255/35R20	97W	XL	BSW	195580	8.5- 9.0 -10.0	27	10.1	26.9	10	12.7	1609	50	360 A A	771
275/30R20	97W	XL	BSW	195790	9.0- 9.5 -10.0	28	10.3	26.5	10.7	12.5	1609	50	360 A A	783
265/35R22	102V	XL	BSW	195540	9.0- 9.5 -10.5	32	10.2	29.4	10.5	13.9	1874	50	360 A A	707

 [Print Complete \(/print-tire-specs/2632\)](/print-tire-specs/2632)

Bold designates measuring rim width

SL = Standard Load, XL = Extra Load, RD = Reinforced, WW = White sidewall, BSW = Black sidewall

Speed rating S = 112 mph, T = 118 mph, H = 130 mph, V = 149 mph, W = 168 mph, Y = 186 mph, (Y) = 195 mph

All Toyo brand tires are subject to continuous development. Toyo Tire U.S.A. Corp. reserves the right to change construction, materials or specifications without notice or obligation. Contact your Toyo Tires dealer or Toyo Tires for current information.